



# Beta10 - 10bhp



MODEL BETA 10

ISO-3046 8665



**2 Cylinders - 479 cc's - 10bhp @ 3000rpm – Weight 89kg**

## Standard Specification

Beta Marine Beta 10 - 2 cylinder, naturally aspirated, diesel propulsion engine developing 10 bhp at 3,000 rpm with a swept volume of 479 cc's. The engine is supplied complete with a heat exchanger and header tank, water cooled exhaust manifold, fresh and sea water pumps, cast injection bend, mechanical fuel lift pump, fuel and oil filters, heavy duty bearers, flywheel with heavy inertia ring for super smooth running at low rpm, flywheel housing, special quiet air intake filter, 12 volt starter, 40 amp battery charging alternator, shutdown solenoid energised to stop, control panel "A" (with keystack switch and pushbutton stop, warning lights and alarm buzzer for low oil pressure, high water temperature, no charge, and power on); a 3m interconnection cable with multi pin plug and sockets to engine harness. Gearbox with nominal 2:1 reduction, heavy duty engine feet with flexible mountings, "Morse" type end fittings for speed and gear control, engine test certificate, operators manual. Red paint and packed on skid base with a 3 year "Self Service" warranty.

- Reliable heat exchanger cooled, naturally aspirated, indirect injection diesel engine, based upon Kubota's highly advanced technology.
- Combined heat exchanger and water cooled exhaust manifold for reliability with cupro-nickel tube stack, phosphor bronze end caps and sacrificial anode.
- Cast iron cylinder head and block with a gear driven camshaft and sea water pump.
- Three vortex combustion system for quiet running, low emissions and excellent fuel consumption.
- Emission compliant in all countries.
- Installation angles up to 15° maximum when static, and 25° when heeling.
- Technodrive or PRM gearboxes. Output rotation is clockwise in ahead viewed from gearbox end.
- Heavy duty power take off to drive auxiliary equipment.

## Engine Options

Special engine feet to suit your installation requirements.  
 Keel cooling.  
 Shallow sump.  
 12 Volt - 70 Amp alternator available.  
 Control Panels ABV, ABVW, B or C with gauges and alarms.  
 See price list for a comprehensive range of accessories to cover a complete engine installation.

Panel A



**Detailed engine drawings, brochures and manuals available under "Downloads"**

**BETA MARINE**

Beta Marine Limited, Davy Way, Waterwells, Quedgeley, Gloucester GL2 2AD, U.K.  
 Tel: +44 (0)1452 723492 Fax: +44 (0)1452 883742 sales@betamarine.co.uk